



TURISMO VELOCE 800 LUSSO



FIRE RED/DARK METALLIC OPAQUE GREY



PEARL WHITE/DARK METALLIC OPAQUE GREY



UNLEADED GASOLINE WITH UP TO 10% ETHANOL ONLY

ENGINE

Type
Timing system
Total displacement
Compression ratio
Starting
Bore x stroke
Max. power - r.p.m. (at the crankshaft)

Three cylinder, 4 stroke, 12 valve
"D.O.H.C" with mechanical chain tensioner
798 cm³ (48.7 cu. in.)
12.3:1
Electric
79 mm x 54.3 mm (3.1 in. x 2.1 in.)
81 kW (110 hp) at 10.150 r.p.m.

Max. torque - r.p.m.
Cooling system

80 Nm at 7.100 r.p.m
Cooling with separated liquid and oil radiators

Engine management system

Integrated ignition - injection system
MVICS 2.0 (Motor & Vehicle Integrated Control System) with three injectors.
Engine control unit Eldor EM2.0, throttle body full ride by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire Torque control with four maps, Traction Control with eight levels of intervention with lean angle sensor

Electronic quick shift

MV EAS 2.1 (Electronically Assisted Shift Up & Down)

Clutch

Hydraulic, wet, multi-disc with slipper clutch

Transmission
Primary drive
Gear ratio

Cassette style; six speed, constant mesh
22/41

First gear: 13/37
Second gear: 16/35
Third gear: 18/32
Fourth gear: 20/30
Fifth gear: 22/29
Sixth gear: 21/25

Final drive ratio

16/41

ELECTRICAL EQUIPMENT

Voltage
Alternator
Battery

12 V
350 W at 5000 r.p.m.
12 V - 11 Ah

DIMENSIONS AND WEIGHT

Wheelbase
Overall length
Overall width
Saddle height
Min. ground clearance
Trail
Dry weight
Fuel tank capacity

1445 mm (56.89 in.)
2125 mm (83.66 in.)
910 mm (35.83 in.)
850 mm (33.46 in.)
140 mm (5.51 in.)
108 mm (4.25 in.)
199 kg (438.72 kg)
21.5 l (5.68 U.S. gal.)

PERFORMANCE

Maximum speed*

230 km/h (143 mph)

FRAME

Type
Rear swing arm pivot plates material

ALS Steel tubular trellis (MAG welded)
Aluminium alloy

FRONT SUSPENSION

Type

Sachs "UPSIDE DOWN" semi-active telescopic hydraulic fork MVCSC (MV Agusta Chassis Stability Control)
43 mm (1.69 in.)
160 mm (6.30 in.)

Fork dia.
Fork travel

REAR SUSPENSION

Type

Progressive Sachs, semi-active single shock absorber with hydraulic spring preload adjustment MVCSC (MV Agusta Chassis Stability Control)
Aluminium alloy
165 mm (6.50 in.)

Single sided swing arm material
Wheel travel

BRAKES

Front brake

Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Brembo radial-type, with 4 pistons
Ø 32 mm (Ø 1.26 in.)

Front brake caliper

Rear brake
Rear brake caliper

Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)

ABS System

Bosch 9 Plus with RLM (Rear wheel Lift-up Mitigation)

WHEELS

Front: Material/size
Rear: Material/size

Aluminium alloy 3.50" x 17"
Aluminium alloy 6.00" x 17"

TYRES

Front
Rear

120/70 - ZR 17 M/C (58 W)
190/55 - ZR 17 M/C (75 W)

FAIRING

Material

Thermoplastic

ORIGINAL EQUIPMENT

Included accessories

Immobilizer - Heated Grips - Bluetooth Cruise control - GPS sensor - Central stand - Adjustable windshield.
Bags* 34 l (8,98 U.S. gal. each)

OPTIONAL

Garmin navigation system

EMISSIONS

Environmental Standard
Combined fuel consumption
CO₂ Emissions

Euro 4
5.8 l/100 km
129 g/km

Every country could have a price variation due to local import duties and taxes.

MY 2020 - 01/11/19

VISIT OUR WEBSITE TO SEE ALL THE AVAILABLE MV AGUSTA SPECIAL PARTS

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.